



----- CHASSIS -----

CHASSIS: NAVISTAR 7400 SFA 4X4
 CAB: 4 DOOR
 ENGINE: INTERNATIONAL DT570 330 HP
 TRANSMISSION: ALLISON 3000EVS-P 5-SPD. AUTO.
 FRONT AXLE: MERITOR MX-12-120 12,000#
 REAR AXLE: MERITOR RS-23-160 23,000#

----- PUMP -----

PUMP: HALE QMAX-150 1500 GPM SINGLE STAGE
 INTAKES
 DRIVER SIDE: 6" & 2-1/2"
 OFFICER SIDE: 6" & 2-1/2"
 FRONT: 6" W/5" PIPE & 5" AIR VALVE
 REAR:
 DISCHARGES: NO DISCHARGES AT DRIVER'S SIDE
 DRIVER SIDE: (1) 4" & (1) 2-1/2"
 OFFICER SIDE: (1) 4" & (1) 2-1/2"
 FRONT: (1) 1-1/2"
 REAR: (1) 3" RIGHT
 DECK GUN: (1) 3" W/13" EXTEND-A-GUN
 OTHER: (2) 1-3/4" CROSSLAWS (LOWEDED)
 (1) 2-1/2" CROSSLAW (LOWEDED)

----- TANK -----

TANK: UPF POLY IBE
 WATER: 500 GALLONS
 FOAM: 40 GALLONS
 EXTRA FILLS: 2-1/2" BETTS AT R/H SIDE REAR
 DUMPS:

----- BODY -----

BODY TYPE: 101" INTERFACE W/ROOF COMPTS.
 MATERIAL: 3/16" ALUMINUM
 COMPARTMENTATION
 DRIVER SIDE: FULL HEIGHT/SPLIT DEPTH
 OFFICER SIDE: FULL HEIGHT/SPLIT DEPTH
 HOSEBED
 CAPACITY: 100 CU. FT.
 DIVIDERS: TWO (2)
 HOSE LOADS: 1,000' of 5" HOSE
 300' of 3" HOSE
 300' of 2-1/2" HOSE
 ----- MISC. -----
 GENERATOR: HARRISON 10.0MAS 10KW PTO HYD
 FOAM SYSTEM: PNEUMAX SILVER SERIES 140SP (CAFS)

CUSTOMER APPROVAL:

NAME:

TITLE:

DATE:

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS. CONTRACT SPECIFICATIONS SHALL PREVAIL OVER DRAWING.

SYM	DATE	REVISION DESCRIPTION	APP'D
B	10-24-06	PER APPROVED PRE-CON LETTER	B.Y.
A	7-28-06	REVISED PER PRE-CONSTRUCTION	B.Y.

SALES ENGINEER : BILL YURICK



KOVATCH MOBILE EQUIPMENT
 ONE INDUSTRIAL COMPLEX - NESQUEHONING, PA 18240

DIMENSIONS ARE APPROXIMATE & MAY VARY DUE TO BUILD ADJUSTMENTS

DATE: 4-28-06 SCALE: 1"=24" DWG SIZE: D DRAWN BY: JIM APPROVED BY: BY

KME COMMERCIAL PUMPER

MT. AETNA VFD, MD

GSO#6606